



## BARRA FISSA CM.60 DX/SX SERIE NYLON Ø35

fixed bar cm.60 rh/lh series Nylon Ø35

	cm	Kg
AN-B02/XX	60	2,3



bianco lucido RAL 9016	blu lucido RAL 5002	verde lucido RAL 6005	giallo lucido RAL 1003	rosso lucido RAL 3002	grigio lucido RAL 7004	nero lucido RAL 9005
01	02	03	04	05	06	07

### testo di capitolato:

barra fissa orizzontale di sicurezza Ø35 mm, universale dx/sx con rinforzo laterale di portata, realizzata in tubo di alluminio 2 mm., rivestita con materiale termoplastico nylon (poliammide 6), spessore 2 mm, caldo al tatto, unita con giunti di innesto in nylon e barra filettata in acciaio, completa di: vite svasata di unione Ø8, piattelli per fissaggio in nylon, a 6 fori, rosoni acciaio inox funzione "antivandalo". dimensione mm 600(p) x 212(l) x 225(h).

tipo Goman codice AN-B02/XX

### specifications:

fixed horizontal safety bar Ø35 mm, universal right/left with side reinforcement of capacity, made of 2 mm aluminum tube, coated with thermoplastic nylon (polyamide 6), thickness 2 mm, warm to the touch, nylon couplings and steel threaded bar, complete with: Ø8 countersunk union screw, nylon fixing plates, 6 holes, stainless steel roses "vandal-proof" function. dimension mm 600 (p) x 212 (l) x 225 (h). type Goman code AN-B02/XX

